



TECHNICAL DATA	STANDARD			
<b>EXTERNAL DIMENSIONS</b>				
width	460 mm			
depth	545 mm			
height	715 mm			
<b>WEIGHT</b>				
38 kg				
<b>VOLTAGE</b>				
230V 50Hz				
<b>POWER REQUIRED</b>				
3200 W				
<b>WATER HARDNESS</b>				
2-8 °F				
<b>INLET WATER PRESSURE</b>				
200-400 kPa				
<b>CROCKERY DIMENSIONS</b>				
plates diameter	295 mm			
glasses max. height	305 mm			
<b>RACK DIMENSIONS</b>				
400X400 mm				
<b>RACK EQUIPMENT</b>				
2XC121 - 1X10728 - 1X15060				
<b>WASHING CYCLES</b> (s)				
	1<60>	2<90>	3<120>	4<180>
<b>WATER SUPPLY 55°C</b>				
racks/h(*) <sup>(1)</sup>	60	40	30	20
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(1)</sup>	16	16	16	16
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)				
1.8 L				
<b>BOILER CAPACITY</b>				
3.4 L				
<b>BOILER HEATING ELEMENT</b>				
2800 W				
<b>RINSING TEMPERATURE (SET)</b>				
85°C				
<b>TANK CAPACITY</b>				
15.5 L				
<b>TANK HEATING ELEMENT</b>				
1250 W				
<b>TANK TEMPERATURE (SET)</b>				
55°C				
<b>PUMP POWER</b>				
400 W (185 L/min)				
<b>DRAIN PUMP (optional)</b>				
25W h MAX scarico 0.8m (40 L/min <sup>***</sup> )				
<b>NOISE</b>				
61.2 (dB(A)±0.7)				

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.