



TECHNICAL DATA					
<b>EXTERNAL DIMENSIONS</b>					
width	690 mm				
depth	800 mm				
height	1890/2270mm (door open)				
WEIGHT(basic version)	155 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	8000 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
<b>CROCKERY DIMENSIONS</b>					
size allowed	805 mm				
<b>RACK DIMENSIONS</b>					
550X665 mm					
<b>RACK EQUIPMENT</b>					
1XC86/A - 1XC87/B - 1XC97/A - 1XC100					
WASHING CYCLES (s)	1 (120)	2 (240)	3 (360)	4 (480)	----
<b>WATER SUPPLY 55°C</b>					
racks/h(*) <sup>(1)</sup>	30	15	10	7,5	--
<b>WATER SUPPLY 10°C</b>					
racks/h(*) <sup>(1)</sup>	15	15	10	7,5	--
WATER CONSUMPTION / CYCLE	4,2 l				
BOILER CAPACITY	15 l				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	50 l				
TANK HEATING ELEMENT	3000 W				
TANK TEMPERATURE (SET)	60°C				
WASHING PUMP POWER	2000 W (810 l/min <sup>***</sup> )				
RINSING PUMP POWER	250 W (150 l/min <sup>***</sup> )				
DRAIN PUMP (optional)	190 W (120 l/min <sup>***</sup> )				
ACOUSTIC PRESSURE	63.8 dB(A)				

(\*) STANDARD TERMOSTOP (CAN NOT BE DISABLED)

(\*\*\*) MAXIMUM FLOW RATE

**- STANDARD ENERGY SAVING (CAN NOT BE DISABLED)**

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.