



| TECHNICAL DATA | STANDARD | | | | |
|---|--|-----------|-----------|-----------|------|
| EXTERNAL DIMENSIONS | | | | | |
| width | 590 mm | | | | |
| depth | 600 mm | | | | |
| height | 1290 mm | | | | |
| WEIGHT | 68.5 kg | | | | |
| VOLTAGE | 400V 3N 50Hz | | | | |
| POWER REQUIRED | 6900 W | | | | |
| WATER HARDNESS | 2-8 °F | | | | |
| INLET WATER PRESSURE | 200-400 kPa | | | | |
| CROCKERY DIMENSIONS | | | | | |
| plates diameter | 380 mm | | | | |
| glasses max. height | 355 mm | | | | |
| RACK DIMENSIONS | 500X500 mm | | | | |
| RACK EQUIPMENT | 1XC40 - 1XC44 - 1X15060 | | | | |
| WASHING CYCLES (s) | 1(60) | 2(90) | 3(120) | 4(180) | ---- |
| WATER SUPPLY 55°C | | | | | |
| racks/h ^(*) (¹) | 60 | 40 | 30 | 20 | -- |
| WATER SUPPLY 10°C | | | | | |
| racks/h ^(*) (¹) | 26 | 26 | 26 | 20 | -- |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | 2.3 L | | | | |
| BOILER CAPACITY | 5.7 L | | | | |
| BOILER HEATING ELEMENT | 6000 W | | | | |
| RINSING TEMPERATURE (SET) | 85°C | | | | |
| TANK CAPACITY | 29 L | | | | |
| TANK HEATING ELEMENT | 2700 W | | | | |
| TANK TEMPERATURE (SET) | 55°C | | | | |
| PUMP POWER | 900 W (500 L/min ^{***}) | | | | |
| DRAIN PUMP (optional) | 25 W h MAX drainig 0.8m (40 L/min ^{***}) | | | | |
| NOISE | 63 dB(A) | | | | |

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

 (¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.